

Pioneer

GS-WAVE SERIES

A 3-metre high dancefloor stack with wide dispersion and a high SPL across a broad frequency range; delivers a powerful, warm sound that combines a resonant bass and tight chest kick with crystal clear high frequencies.



WAV-TWPOD

Omnidirectional super tweeter pod



FEATURES

- Super tweeter pod
- Reproduces UHF from overhead
- Expands the depth of the system

SPECIFICATION

| | |
|----------------------|---|
| Enclosure Type | Omnidirectional tweeter array |
| Frequency Response | 5 kHz to 20 kHz |
| Sensitivity (1w/1m) | 100 dB |
| Nominal Impedance | 8 Ω |
| Power Handling | 100 W RMS, 200 W program |
| Maximum SPL | 120 dB cont., 126 dB peak |
| Dispersion | Omnidirectional |
| Driver Configuration | 4 x 1.5 inch (38 mm) exit ferrite compression bullet tweeters |
| Connectors | 1 x Neutrik SpeakON™ NL4MPR |
| Dimensions (WxDxH) | 226 x 201 x 226 mm (8.9 x 7.9 x 8.9 inch) not including eyebolts |
| Weight | 10 kg (22 lb) |
| Enclosure | 18 mm (0.7 inch) birch plywood |
| Finish | Impact-resistant, black textured polyurethane |

